# **TECHNICAL DATA SHEET**

EN 149:200

1100 FFP1 NR

4 x OEL protection level (Acording to Npf)

Building, Ship building,

Pharmaceutical industry,

Engineering, Iron and steel,

Agriculture, Coal mining, etc.

The disposable flat fold respirator

Particles are filtered through

the melt blown filter.

10 gr

consists of several layers of material.

**Horizontal Folding Series** 

**ERA** 



#### Components and materials

The following mate the production of th	
Component	Material
Filter material	Polypropylene
Head Straps	TPE (Thermo plastic elastomer) Latex free head band
Nose clip	Polypropylene

#### Maximum Filter Penetration

EN149:2001+A1:2009	Maximum Filter		
Classification	Penetration		
FFP1	20%		

#### **Total inward leakege**

EN149:2001+A1:2009	Maximum Total Inward		
Classification	Leakage		
FFP1	22%		

#### Breathing resistance

EN 149:2001+A1:2009 Classification	Maximum Breathing Resistance Inhalation Inhalation Exhalation at 301/min at 951/min at 1601/min			
FFP1	0.6 mbar	2.1 mbar	3.0 mbar	

## Clogging

For single shift use respirators (NR), the clogging test is optional. For re-usable respirators this test is mandatory. The respirators are loaded with very high amount of Dolomite dust which will tend to clog the filter. After loading with the required amount of dust, the breathing resistance of the respirators shall not exceed the following limits

EN 149:2001+A1:2009 Classification	Maximum Breathing Resistance Inhalation at 95l/ Exhalation at min 160l/ min		
FFP1	<ul><li>4.0 mbar (val- ved respirator)</li><li>3.0 mbar (unvalved respirator)</li></ul>	3.0 mbar (valved respirator)	

### **Ordering Information**

Descirption	Barcode	Packing Steel	Pcs In Box	Pcs In Carton	Gross Box	Size of Box
1100 FFP1 NR	8681248449121	Multiple	25	500	5.75 kg	60x38x30 cm

#### Marking

Code Nr

Series

Product Name

**Aplication Limit** 

Places of use

Description

Weight

Working principle

: Reusable R

NR : Non Reusable (single shift use only) D : (Dolomite) Meets the clogging resistance requirements

Maximum Relative Humidity

End of Shelf Life. Date format: YYYY/MM/DD

Tempature Range Name and address of Legal Manufacturer

€ € 2797 EN149.2001+A1.2009 Regulation (EU) 2016/425







Phone: +90 216 394 47 59 pbx

E-mail : export@eratozmaskesi.com - export@eramaske.com web : www.eratozmaskesi.com - www.eramaske.com