TECHNICAL DATA SHEET





| Code Nr | 4110 V FFP1 NR D |
|-------------------|---|
| Product Name | ERA |
| Series | Vertical Folding Series |
| Aplication Limit | 4 x OEL protection level (Acording to Npf) |
| Places of use | Building, Ship building, Pharmaceutical industry, Engineering,Iron and steel, Agriculture, Coal mining, etc. |
| Description | The disposable flat fold respirator consists of several layers of material. |
| Working principle | Particles are filtered through the melt blown filter. |
| Weight | 12 gr |

Components and materials The following materials are used in

the production of the FFP1

| Component | Material | |
|-----------------|---------------|--|
| Filter material | Polypropylene | |
| Head Straps | Knit Rubber | |
| Valve | Polypropylene | |
| Nose clip | Aluminum | |

Maximum Filter Penetration

| EN149:2001+A1:2009 | Maximum Filter | | |
|--------------------|----------------|--|--|
| Classification | Penetration | | |
| FFP1 | 20% | | |

Total inward leakege

| | 2001+A1:2009 ssification | Maximum Total Inward Leakage | | |
|------|-----------------------------|---------------------------------|--|--|
| FFP1 | | 22% | | |

Breathing resistance

| EN 149:2001+A1:2009 Classification | Max Inhalation at 30I/min | | | |
|--|---------------------------------|----------|----------|--|
| | | | | |
| FFP1 | 0.6 mbar | 2.1 mbar | 3.0 mbar | |

Clogging

For single shift use respirators (NR), the clogging test is optional. For re-usable respirators this test is mandatory. The respirators are loaded with very high amount of Dolomite dust which will tend to clog the filter. After loading with the required amount of dust, the breathing resistance of the respirators shall not exceed the following limits

| EN 149:2001+A1:2009 Classification | Maximum Breathing Resistance Inhalation at 95I/ Exhalation at min 160I/ min | | |
|--|--|------------------------------------|--|
| FFP1 | 4.0 mbar (valved respirator) 3.0 mbar (unvalved respirator) | 3.0 mbar (valved respirator) | |

| Ordering Information | | | | | | |
|----------------------|---------------|---------------|------------|---------------|-----------|-------------|
| Descirption | Barcode | Packing Steel | Pcs In Box | Pcs In Carton | Gross Box | Size of Box |
| 4110 V FFP1 NR D | 8681248449381 | Individual | 15 | 270 | 7 kg | 52x72x27 cm |

Marking

: Reusable

NR: Non Reusable (single shift use only)

: (Dolomite) Meets the clogging resistance requirements



End of Shelf Life. Date format: YYYY/MM/DD

Maximum Relative Humidity



Tempature Range



Name and address of Legal Manufacturer











Phone: +90 216 394 47 59 pbx E-mail: export@eratozmaskesi.com web: www.eratozmaskesi.com