



Code Nr	7110 AC V FFP2 NR D
Product Name	ERA
Series	Conical Professional Series AC
Application Limit	12 x OEL protection level (According to Npf)
Places of use	Building, Ship building, Pharmaceutical industry, Engineering, Iron and steel, Agriculture, Coal mining, etc. Medical, Hospital, Droplet aerosols, Protein molecules, Viruses, Bacteria fungi and spores, Asbestos fibers
Description	The disposable flat fold respirator consists of several layers of material.
Working principle	Particles are filtered through the melt blown filter.
Weight	12 gr

Components and materials

The following materials are used in the production of the FFP2

Component	Material
Filter material	Polypropylene
Carbon material	Activated carbon material
Head Straps	Knit Rubber
Valve	Polypropylene
Nose clip	Aluminum (Optional)
Face seal	Polyethylene

Maximum Filter Penetration

EN149:2001+A1:2009 Classification	Maximum Filter Penetration
FFP2	6%

Total inward leakage

EN149:2001+A1:2009 Classification	Maximum Total Inward Leakage
FFP2	8%

Breathing resistance

EN 149:2001+A1:2009 Classification	Maximum Breathing Resistance		
	Inhalation at 30l/min	Inhalation at 95l/min	Exhalation at 160l/min
FFP2	0.7 mbar	2.4 mbar	3.0 mbar

Clogging

For single shift use respirators (NR), the clogging test is optional. For re-usable respirators this test is mandatory. The respirators are loaded with very high amount of Dolomite dust which will tend to clog the filter. After loading with the required amount of dust, the breathing resistance of the respirators shall not exceed the following limits




EN 149:2001+A1:2009 Classification	Maximum Breathing Resistance	
	Inhalation at 95l/min	Exhalation at 160l/min
FFP2	5.0 mbar (valved respirator)	3.0 mbar (valved respirator)
	4.0 mbar (unvalved respirator)	

Ordering Information

Description	Barcode	Packing Steel	Pcs In Box	Pcs In Carton	Gross Box	Size of Box
7110 AC V FFP2 NR D	8681248449497	Multiple	10	120	4.75 kg	44x45.5x45 cm

Marking

R : Reusable
 NR : Non Reusable (single shift use only)
 D : (Dolomite) Meets the clogging resistance requirements

 End of Shelf Life. Date format: YYYY/MM/DD	 Temperature Range
 Maximum Relative Humidity	 Name and address of Legal Manufacturer

CE 2797
 EN149:2001+A1:2009
 Regulation (EU) 2016/425

UK CA 0086
 EN149:2001+A1:2009
 PPE:2016/425 On Personal Protective Equipment

bsi.

ISO
 9001:2015

bsi

10 YEARS
 ANNIVERSARY